



## C Type Panel Wall-mounted Specification

Model APFCW-			250	300	400	500	600	
Air flow	H/M/L	m <sup>3</sup> /h	425/360/320	510/430/380	680/580/510	850/720/640	1020/870/770	
	H/M/L	CFM	250/210/190	300/250/220	400/340/300	500/420/380	600/510/450	
Cooling	Capacity	H/M/L	kW	2.2/1.84/1.65	2.64/2.24/2.05	3.08/2.62/2.27	4.07/3.73/3.24	4.45/4.18/3.74
	Water flow rate	H	l/h	378	454	530	700	765
	Water pressure drop	H	kPa	12	18	22	26	29
Heating	Capacity	H/M/L	kW	3.02/2.6/2.23	3.69/3.25/2.77	4.34/3.86/3.25	5.69/5.12/4.32	6.3/5.67/4.73
	Water pressure drop	H	kPa	10	16.4	20.8	25.1	27.9
Power supply		V/ph/Hz	220-240/1/50					
Power input		H	W	28	40	44	50	60
Sound pressure level		H/M/L	dB(A)	30/24/20	35/29/24	37/31/26	39/33/28	40/34/29
Fan motor	Type		Low noise 4-speed fan motor					
	Quantity		1					
Fan	Type		Tangential fan					
	Quantity		1					
Coil	Row		2					
	Max. Working pressure		MPa	1.6				
	Diameter		mm	Φ7				
Body	Dimensions	W×H×D	mm	915×210×290	915×210×290	915×210×290	1070×210×316	1070×210×316
	Packing	W×H×D	mm	1020×300×385	1020×300×385	1020×300×385	1180×300×410	1180×300×410
	Net weight		kg	12	12	12	15	15
	Gross weight		kg	16	16	16	19	19
Pipe connection	Water inlet/outlet pipe		Inch	G3/4				
	Drain pipe		mm	ODΦ20				