



F4 Floor standing

Specification

Model			APFR4E-60CS	APFR4E-60HS
Capacity	Cooling Capacity	Btu/h	60000	60000
		kW	17.6	17.6
	Heating Capacity	Btu/h	—	66500
		kW	—	19.5
Electrical Parts	Power Supply(V~,Hz,Ph)		380,50,3	380,50,3
	Power Input (W)h	Cooling	7250	7250
		Heating	—	7200
	Operating Current (A)	Cooling	12.5	12.5
Heating		—	10.9	
Performance	EER (Btu/W.h, W/W)		2.41	2.41
	COP (W/W)		—	2.71
	Air Flow Volume (m3/h)	Indoor	2200	2200
		Indoor(Hi/Med/Lo)	54/51/48	54/51/48
	Noise Level (dB(A))	Indoor	60	60
		Outdoor	60	60
Ambient Temp ()		18-56	-7-56	
Applicable Area (m2)		100-150	100-150	
Dimension & Weight	Net Dimension (mm)	Indoor (WxHxD)	600x1900x358	600x1900x358
		Outdoor (WxHxD)	900x1170x350	900x1170x350
	Net Weight (kg)	Indoor/Outdoor	65/100	65/104
	Packing Dimension (mm)	Indoor (WxHxD)	680x1985x450	680x1985x450
		Outdoor (WxHxD)	1032x1307x443	1032x1307x443
	Gross Weight (kg)	Indoor/Outdoor	75/105	75/109
	Piping Size (mm(inch))	Liquid	Ø12.7(1/2)	Ø12.7(1/2)
		Gas	Ø19(3/4")	Ø19(3/4")
Stuffing Quantity (Set)	20'/40'/40'HQ	20/45/56	20/45/56	

Remark:

- 1.The above design and specifications are subject to change of product improvement without prior notice.
- 2.The noise level data reflects the level in anechoic chamber.